



elock-1200 / elock-1200L

## Features


**elock-1200 Series** electromagnetic locks offer cost effective solution with easy installation & suitable for variety of application. It has no moving parts thus keeping maintenance to a minimum.

All types of brackets are available to ease installation for both in-swing & out-swing doors.

## Specification

- 1200lbs holding force
- Dual voltage 12 & 24 Vdc
- Current drawn 500mA / 250mA
- MOV surge protection
- Fail-Safe type
- Unmonitored Model ( elock-1200 )  
& Monitored Model ( elock-1200L )
- Push-off button on armature for instant release
- Dimension : -  
Magnet : 265(L) X 66(W) X 40(D) mm  
Armature Plate : 185(L) X 60(W) X 17(D) mm


## User Guide



## Optional Brackets


### EL-BKL ( L Bracket )

- Adjustable "L" bracket for outward door when the header is narrow.
- Available for eLock-300, 600 & 1200 Series



### EL-BKZ ( ZL Bracket )


- Adjustable "ZL" bracket for inward door application.
- Available for eLock-300, 600 & 1200 Series application.



## Mounting Diagram


### Standard Mounting:

- With Filler Plate attached on top of EM Lock.



### L Bracket Mounting :

- Mounting with "Adjustable L Bracket" when Door frame is narrow.
- Mounting Procedure :-  
Remove the original "Filler Plate" attached to EM Lock, replaced with " Adjustable L Bracket " set.



### ZL Bracket mounting :

- Mounting with " ZL Bracket " for In-swing door application.
- Mounting Procedure :-  
Remove the original "Filler Plate" attached to EM Lock, replaced with " Adjustable ZL Bracket " set.

