



7" TFT LCD Touch Screen Display



FX-300/700G9

• Key Features:

- 7" TFT LCD Touch Screen Display, Handsfree
- Except HK5, others are no keypad,
- Now all 700 indoor monitor can support SIP
- 700HK5 also support Home automation and Multimedia
- Only support AGC and AEC
- SIP 2.0
- Home Automation
- Multimedia Support
- IP Indoor Monitor
- Internal Microphone & Speaker
- H.264 Video Codec Support
- G.711A & G.711U Audio Codec Support
- Alarm Integration
- Receiving Messaging From Center Management Software
- IP Camera Monitoring Support
- Visitor Picture Record
- SD Card Support - SD Card Upgrade
- Full - Duplex Audio Transmission
- Zone 8 will be used for door - bell (Optional)
- Extendable 16 Alarm Input (With additional module)

Technical Specifications:

Model		FX-300/700G9
Cabling Type		UTP
Display		7" TFT LCD
Display Type		Resistive
Touch Screen		Yes
IP Camer Support		8 Camera
Different Ring Tones		4
Visitor Picture Record		Yes
Remote Management		Yes
Remote Contact Control		Yes
Paralel Connection Support		Yes
SD Card Support		Yes (Maximum 32 GB)
Audio Codec		Two-Way G.711U, G.711A
Home Automation		Optional
Multimedia		Optional
Camera	Sensor	No
	Resolution	No
Video Quality	Video Codec	H.264
	Resolution	VGA @ 30fps
	Adjustable Bit Rate	CBR
Video Stream	Stream 1	H.264
	Stream 2	-
Alarm	Alarm input	8
	Alarm Output	1
IP Class		
Network	Ethernet Protocol	Ethernet(10/100Base-T) RJ-45 Connector TCP/IP/ RTSP/ RTP/ ONVIF/ HTTP
	Web Browser	Microsoft Internet Explorer 6.0 or Higher
Software	Secure	Admin Password
	Upgrade	SD Card, Remote Upgrade Tool
	Working	-10 °C ~ +55 °C
Temperature	Storage	-10 °C ~ +55 °C
	Voltage	PoE (IEEE802.3 af) & DC12V or DC12V
Power	Power Consumption	6W
	Physical	Dimension (G x Y x D)

Specifications are subject to change without prior notice