



1.3 Mega 1/4"OV CMOS Network HD IR Cylinder Camera



● FEATURES:

- H.264/MJPEG
- 720P full real time recording
- Support I8S, plug and play
- Support mobilephone, IE browser
- With the same function as POE, better for NVR kit
- Gimbal cable bracket included
- IP66, Lightning-proof, DC12V



CCTV

● SPECIFICATION :

Model	FX-IP102B
GENERAL	
Sensor	1/4" OV 1.3 mega Progressive scan CMOS
Min.illumination	0Lux/F1.4(IR ON)
Electronic shutter	Auto/Manual(1/25~1/10000)
Day/Night	Auto/B/W/Color/EXT
Video Parameter	DWDR, Mirror, 3D Noise reduction, Sharpness/Lightness adjustable
IR distance	20-30M (30xΦ5 IR leds)
Lens	3.6mm M12 Lens
Lens interface	M12
AUDIO/VIDEO COMPRESSION	
Video compression	H.264/MJPEG
Encoding Features	Dual-stream;;Main stream PAL:1280X720 25fps;NTSC:1280X720 30fps
Max. image resolution	1280X720
Encoding System	Constant bit rate,Variable bit rate optional
Video Bit rate	16Kbps-8000Kbps
Stream Type	Complex stream/Video stream
Audio Compression	G.711A
NETWORK	
Password protection	Support
Character display	Support(Channel, Date)
Mobile surveillance	Apple, Android
Protocol	TCP/IP,UDP,HTTP,DHCP,RTP/RTSP,DNS,DDNS,NTP,PPPOE,UPNP,SMTP
Port protocol	I8S,ONVIF,I8
INTERFACE	
Network Interface	RJ45 10M/100M adaptive
GENERAL	
Operating Conditions	-20°C ~ 55°C/0%-90%
IP Grade	IP66
Power Supply	DC12V /POE
Power Consumption	<6W
Dimensions	Φ66(W)*66H)*166.7(L)mm
Weight(net weight)	366g