





1.3 Mega 1/3" SONY CMOS IR HD IP Cylinder Camera



● KEY FEATURES:

- Encoding System: H.264/MJPEG
- 960P full real time recording
- Support ONVIF
- Support mobilephone, WEB, client , Platform management software surveillance
- Talk-back, Alarm, Snapshot, Email
- Support 1ch analog video output
- POE
- Gimbal cable bracket included
- IP66, Lightning-proof, DC12V

CCTV

● SPECIFICATIONS:

Model	FX-IP109B
Sensor	1/3"SONY 1.3mega progressive scan CMOS sensor
Min.illumination	0Lux(IR ON)
Electronic shutter	Auto/Manual(1/25~1/10000)
Day/Night	Auto/Color/B/W/EXT
Video Parameter	DWDR, Mirror, 3D Noise reduction, Sharpness/Lightness adjustable
IR Distance	20-30M(36xΦ5 IR leds)
Lens	6mm M12 Lens(3.6mm /8mm Lens optional), ICR module
Lens interface	M12
AUDIO/VIDEO COMPRESSION	
Video compression	H.264/MJPEG
Encoding Features	Dual-stream; Main stream PAL: 1280X960 25fps; NTSC: 1280X960 30fps
Max. image resolution	1280X960
Encoding System	Constant bit rate,Variable bit rate optional
Video Bit rate	16Kbps~8000Kbps
Stream Type	Complex stream/Video stream
Audio Compression	G.711A
Audio Bit rate	64Kbps
NETWORK	
Motion detection	Single detection zone can be set , Multi-level sensitivity can be set
Privacy zones	4 zones
WDR	Support D-WDR
Snapshot	Support JPEG format, max. resolution based on encoding resolution
Password protection	Support
Character display	Support(Channel、Date)
Alarm function	Video loss, Network anomaly, Tampering alarm, Storage exception
Mobile surveillance	Apple, Android
Protocol	TCP/IP, UDP, HTTP, DHCP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP
Port protocol	I8, ONVIF , I8S optional
Snapshot	Support JPEG format, max. resolution based on encoding resolution
Password protection	Support
Character display	Support(Channel、Date)
Alarm function	Video loss, Network anomaly, Tampering alarm, Storage exception
INTERFACE	
Network Interface	Rj45 10M/100M adaptive
GENERAL	
Operating Conditions/humidity	-20°C ~ 55°C/0%-90%
IP Grade	IP66
Power Supply	DC12V
Power Consumption	<10W
Dimensions	Φ 77(W)*109(H)*211(L)mm
Weight	about 700g

>> Specifications are subject to change without prior notice