



OUTDOOR PANEL



FX-P602-A1



FX-P602-A3

INDOOR MONITOR



FX-AC340-F4



FX-AC470-G7



FX-AC490-G9

Key Features:

1. Video intercom between outdoor panel and indoor monitor
2. Bidirectional communication between indoor monitor, guard station and porter switchboard
3. Handset or hands-free communication
4. Monitor entrance
5. Door unlocking by proximity card or password
6. Optional guard station and porter switchboard

Technical Specifications:

Item	Outdoor panel		Indoor		
Model	FX-P602-A1	FX-P602-A3	FX-AC340-F4	FX-AC470-G7	FX-AC490-G9
Material	Metal surface		ABS plastic		
Camera	Color CCD	Color CCD			
Display	LED/LCD display		3.5"/4" TFT LCD	4"/5.6" TFT LCD	7" TFT LCD
Proximity card reader	IC/ID card reader				
Power supply	Supplied by UPS-DP/P		Supplied by isolator module		
Output voltage	18V		12V & 15V		
Working temperature	-20℃ ~ +55℃				
Capacity	Can connect with 4 outdoor panels in one block at most		Can connect with 99,999 indoor monitors at most		
Installation	Flush mounted		Surface		
Dimension	136*316*56(mm)	155*375*46.5(mm)	225*190*49(mm)	259.7*184.2*54(mm)	239*139*31.2(mm)