

2.43 MEGA PIXEL HD IP DOME CAMERA



● KEY FEATURES:

- H.264 Video Compression (High Definition)
- 1080P full real time recording
- Conforms to ONVIF
- Support mobilephone IE browser, Client, Platform Management software surveillance
- Talkback, Alarm, Snapshot, Email
- Support TF card (32G) storage
- Support 1-ch analog video output
- Vandal Proof Level: IK10 Rated
- Water Proof Level: IP65
- Lighting-proof, 3D bracket adjustable, DC12V
- With POE, D-WDR function
- Lens Size:2.8-12mm Auto Iris Varifocal Lens
- Build in 18pcs IR Led's



● SPECIFICATIONS:

Model	FX-IP520IRV
Sensor	1/2.9" SONY 2.43 mega Progressive scan CMOS
Min.illumintiaon	0Lux/F1.4
Electronic shutter	Auto/Manual (1/25~1/10000)
Day/Night	Auto/B/W/Color/EXT ICR switching
Video Parameter	DWDR, Mirror, 3D Noise reduction, Sharpness/Lightness adjustable
IR distance	10-15M (18xØ5)
Lens	2.8-12mm 3M DC ICR Lens
Lens interface	M14
AUDIO/VIDEO COMPRESSION	
Video compression	H.264
Encoding Features	Dual-stream; Main stream PAL: 1280X720 25fps; NTSC: 1280X720 30fps
Max. image resolution	1920X1080
Encoding System	Constant bit rate, Variable bit rate optional
Video Bit rate	16Kbps-8000Kbps
Stream Type	Complex stream/Video stream
Audio Compression	G.711A
Audio Bit rate	64Kbps
NETWORK	
Motion detection	Can be set to a single detection zone, Multi-level sensitivity can be set
Privacy zones	4 zones
Snapshot	Support JPEG format, max. resolution based on encoding resolution
Password protection	Support
Character display	Support (Channel, Date)
Alarm function	Video loss, Network disconnect, Tampering alarm, Storage exception
Mobile surveillance	Apple, Android
Protocol	TCP/IP, UDP, HTTP, DHCP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP
Port protocol	18, ONVIF
INTERFACE	
Network Interface	Rj45 10M/100M adaptive
Analog video output	1ch CVBS analog video output
Bidirectional-talk input	1CH
Audio output	1CH
Alalarm input/output	2CH/1CH
Communication Interface	RS485
GENERAL	
Operating Conditions	'-10°C ~ 55°C/0%-90%
IP Grade	IP65
Power Supply	DC12V /POE optional
Power Consumption	<5W
Dimensions	112(H)*150(L)mm
Weight	940 g

>> Specifications are subject to change without prior notice